## **VALTRA (VALMET) A SERIES A85L** (2004-2008)



ENGINE Sisu 33DTA Capacity: 7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 500 hours/ 12 months		
USE		CLIMATE

Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
		I

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT Capacity: 6,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
<u></u>	·

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 500 hours, change every 1000 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 1,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
Check every 500 hours, change every 1000 hours/ 12 months	

## **VALTRA (VALMET) A SERIES A85L** (2004-2008)



TRANSMISSION Capacity: 32 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Check every 500 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM Capacity: 25-35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check event 500 hours, change event 1000 hours / 12 months		

Check every 500 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 500 hours, change every 2000 hours/ 24 months

COOLING SYSTEM Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change eve	rv 2000 hours/ 24 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.