

VALTRA (VALMET) T SERIES T191H HITECH (2009-2010)



ENGINE Sisu 74CTA-4V
Capacity: 19 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
More than 5% biodiesel	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 1,5 liter (Industrial), Capacity: 1 liter (Standard)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 1000 hours/ 12 months

POWER TAKE OFF FRONT
Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 500 hours, change every 1000 hours/ 12 months

VALTRA (VALMET) T SERIES T191H HITECH (2009-2010)



TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 55 liter, Capacity: 65 liter ('extra max' capacity)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 250 hours, change every 2000 hours/ 24 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,2-0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 250 hours, change every 2000 hours/ 24 months

COOLING SYSTEM

Capacity: 31 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.