

# VALTRA (VALMET) T SERIES T191LS ADVANCE (2009-2010)



**ENGINE** Sisu 74CTA-4V  
Capacity: 19 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
More than 5% biodiesel	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 250 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 500 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 1,5 liter (Industrial), Capacity: 1 liter (Standard)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 500 hours, change every 1000 hours/ 12 months*

**POWER TAKE OFF FRONT**  
Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

*Check every 500 hours, change every 1000 hours/ 12 months*

# VALTRA (VALMET) T SERIES T191LS ADVANCE (2009-2010)



## TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 55 liter, Capacity: 65 liter ('extra max' capacity)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

Check every 50 hours, change every 1000 hours/ 12 months

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Check every 250 hours, change every 2000 hours/ 24 months

## COOLING SYSTEM

Capacity: 31 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.