## **VALTRA (VALMET) X SERIES X95** (2000-2005)



ENGINE 420 DWRE Capacity: 13 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Dieselfleet LSP Ultra 10W-30	Multifleet SHPD 10W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Dana Capacity: 8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 500 hours, change every 1000 hours	·

HUB REDUCTIONS FRONT Capacity: 1,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 500 hours, change every 1000 hours	·

KROON-OIL B.V. Postbus 149 7600 AC Almelo

## **VALTRA (VALMET) X SERIES X95** (2000-2005)



TRANSMISSION/HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		
Check every 50 hours, change every 1000	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 50 hours, change every 1000	hours	

HYDRAULIC BRAKE SYSTEM Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Chook ayan, 250 hayra ahanga ayan,	2000 hours	·

Check every 250 hours, change every 2000 hours

HYDRAULIC CLUTCH SYSTEM Capacity: 0,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 250 hours, change every 2000 hours

GREASE POINTS/NIPPLES USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

## VALTRA (VALMET) X SERIES X95 (2000-2005)



COOLING SYSTEM Capacity: 15,5-19,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	/ 2000 hours	

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.