

# VALTRA (VALMET) T4 ACTIVE T154 A (ACTIVE) (2014-2021)



**ENGINE** Sisu 66AWF  
Capacity: 19 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 600 hours*

USE	CLIMATE
Biodiesel, first generation (7%)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 250 hours*

## DIFFERENTIAL FRONT

Capacity: 8,5 liter (Dana 740/560), Capacity: 8,5 liter (Dana 740/561), Capacity: 8,5 liter (Dana 750/570), Capacity: 8,5 liter (Dana 755/509), Capacity: 8,5 liter (Dana 755/510)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 600 hours, change every 1200 hours/ 12 months*

## HUB REDUCTIONS FRONT

Capacity: 2 liter (Dana 740/560), Capacity: 2,7 liter (Dana 740/561), Capacity: 2,2 liter (Dana 750/570), Capacity: 2,2 liter (Dana 755/509), Capacity: 2,8 liter (Dana 755/510)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 600 hours, change every 1200 hours/ 12 months*

## POWER TAKE OFF FRONT

Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

*Check every 50 hours, change every 600 hours*

# VALTRA (VALMET) T4 ACTIVE T154 A (ACTIVE) (2014-2021)



## TRANSMISSION

Capacity: 74 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Check every 10 hours, change every 600 hours*

## HYDRAULIC SYSTEM

Capacity: 40 liter (Auxiliary hydraulics), Capacity: 62 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Check every 10 hours, change every 1200 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46***Check every 10 hours, change every 1200 hours/ 12 months*

## COOLING SYSTEM

Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Check every 10 hours, change every 2400 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.