

# VOLVO BM VALMET ALL MODELS 2200

## (1979-1983)



**ENGINE D 39 T**  
Capacity: 8 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

PRODUCT RECOMMENDATION 2

**HDX 30***Change every 125 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20**

PRODUCT RECOMMENDATION 2

**HDX 20W-20***Change every 125 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40***Change every 125 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W**

PRODUCT RECOMMENDATION 2

**HDX 10W***Change every 125 hours*

**TRANSMISSION/HYDRAULIC SYSTEM 8/4**  
Capacity: 34 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Change every 800 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 2

**MP Lithep Grease EP 2***Check every 25 hours*

# VOLVO BM VALMET ALL MODELS 2200

## (1979-1983)



### GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

*Check every 50 hours, change every 1000 hours*

### COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*