## YANMAR DIESEL ENGINES LA L60AE-S, L60A(C)E-D, L60AE-SE, L60A(C)E-DE (1995 AND AFTER)



Capacity: 1,1 liter  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SHPD 15W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  CLIMATE  Moderate  Moderate  PRODUCT RECOMMENDATION 2  Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  CLIMATE  COID  CLIMATE  CLIMATE  COID  CLIMATE  COID  CLIMATE  COID  CLIMATE  COID  CLIMATE  COID  CLIMATE  COID  COID  CLIMATE  COID  CLIMATE  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  CLIMATE  COID  COID  COID  COID  CLIMATE  COID  COID  COID  COID  COID  CLIMATE  COID  COID  COID  COID  CLIMATE  COID	AND ALTER)		
Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SHPD 15W-40  Change every 200 hours/ 3 months  USE  CLIMATE  Moderate  Moderate  Moderate  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  Normal  Normal  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Cold  PRODUCT RECOMMENDATION 2  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Tropical  Tropical  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Tropical  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Tropical  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Multifleet SCD 30  CLIMATE  Multifleet SCD 40  CLIMATE  Multifleet SCD 30  CLIMATE  Multifleet SCD 40  CLIMATE  Multifleet SCD 30  CLIMATE  Multifleet SCD 40  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1  Multifleet SCD 30	ENGINE Capacity: 1,1 liter		
REPODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 200 hours/ 3 months  USE  NOrmal  PRODUCT RECOMMENDATION 1  Multifleet SHPD 15W-40  Change every 200 hours/ 3 months  USE  NOrmal  RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  NOrmal  RECOMMENDATION 1  Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  NOrmal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  NOrmal  PRODUCT RECOMMENDATION 2  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  NOrmal  Cold  PRODUCT RECOMMENDATION 2  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Tropical  Tropical  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  LIMATE  Tropical  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean	USE		CLIMATE
Multifleet SCD 40  Change every 200 hours/ 3 months  USE Normal PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40 Multifleet SCD 30  Change every 200 hours/ 3 months  USE Normal Normal Moderate  PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE Normal PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE Normal PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE Normal PRODUCT RECOMMENDATION 2 Multifleet SCD 10W  Change every 200 hours/ 3 months  USE CLIMATE Tropical PRODUCT RECOMMENDATION 1 Multifleet SCD 40  Change every 50 hours  USE USE USE USE UNIMATE Initial service PRODUCT RECOMMENDATION 2 Multifleet SCD 30  Change every 50 hours  USE USE UNIMATE Multifleet SCD 40  Change every 50 hours  USE USE USE USE USE USE USE USE USE US	Normal		Tropical
Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  Normal  Cold  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Cold  PRODUCT RECOMMENDATION 2  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  Initial service  Multifleet SCD 30  Change every 50 hours  USE  Initial service  Multifleet SCD 30  Change every 50 hours  USE  Initial service  Multifleet SCD 30  Change every 50 hours  USE  Initial service  Multifleet SCD 30  Change every 50 hours  USE  Initial service  Multifleet SCD 30  CLIMATE  Multifleet SCD 30  CLIMATE  Multifleet SCD 30  CLIMATE  Multifleet SCD 30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 1		
Normal Normal Normal Negopuct recommendation 2 Multifleet SHPD 15W-40 Multifleet SCD 30  Change every 200 hours/ 3 months USE Normal No	Multifleet SCD 40		
Normal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2  Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Tropical  Tropical  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Tropical  Multifleet SCD 40  Change every 50 hours  USE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Moderate  PRODUCT RECOMMENDATION 1	Change every 200 hours/ 3 months		
Multifleet SHPD 15W-40  Multifleet SCD 30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Moderate  PRODUCT RECOMMENDATION 2  Moderate  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  CLIMATE  Cold  PRODUCT RECOMMENDATION 2  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Tropical  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE  Initial Service  PRODUCT RECOMMENDATION 1  Multifleet SHPD 15W-40  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30	USE		CLIMATE
Multifleet SHPD 15W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 1  Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Cold  Change every 200 hours/ 3 months  USE  CLIMATE  Tropical  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 2  Multifleet SCD 30	Normal		Mediterranean
Change every 200 hours/ 3 months  USE  NOrmal  PRODUCT RECOMMENDATION 1  Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  NOrmal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Change every 200 hours/ 3 months  USE  NOrmal  PRODUCT RECOMMENDATION 2  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Cold  PRODUCT RECOMMENDATION 2  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  LIMATE  Tropical  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  LIMATE  Miltial service  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Moderate  Moderate  PRODUCT RECOMMENDATION 2  Multifleet SCD 30		PRODUCT RECOMMENDATION 2	
Normal Normal Normal Normal Normal Normal Noderate Normal Noderate Normal Noderate Normal Nultifleet SHPD 10W-40  Change every 200 hours/ 3 months USE Normal Norma	Multifleet SHPD 15W-40	Multifleet SCD 30	
Normal Moderate  PRODUCT RECOMMENDATION 2  Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 2  Multifleet SHPD 10W-40  Cold  PRODUCT RECOMMENDATION 2  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  CLIMATE  Tropical  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Tropical  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Moderate  Moderate  PRODUCT RECOMMENDATION 2	Change every 200 hours/ 3 months		
PRODUCT RECOMMENDATION 2 Kroontrak MTH 10W-30  Change every 200 hours/3 months  USE  Normal  PRODUCT RECOMMENDATION 2 Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/3 months  USE  CLIMATE Cold  PRODUCT RECOMMENDATION 2 Multifleet SCD 10W  Change every 200 hours/3 months  USE  CLIMATE Tropical  PRODUCT RECOMMENDATION 1 Multifleet SCD 40  Change every 50 hours  USE  CLIMATE Tropical  Multifleet SCD 40  Change every 50 hours  USE  CLIMATE Mediterranean  PRODUCT RECOMMENDATION 1 Multifleet SCD 30  Change every 50 hours  USE  CLIMATE Mediterranean  PRODUCT RECOMMENDATION 2 Multifleet SCD 30  Change every 50 hours  USE  CLIMATE Mediterranean  PRODUCT RECOMMENDATION 2 Multifleet SCD 30  Change every 50 hours  USE  CLIMATE Moderate Moderate  PRODUCT RECOMMENDATION 2	USE		CLIMATE
Kroontrak MTH 10W-30  Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  LIMATE  CLIMATE  Tropical  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  LIMATE  Tropical  CLIMATE  Tropical  Multifleet SCD 40  Change every 50 hours  USE  LIMATE  Multifleet SCD 40  Change every 50 hours  USE  LIMATE  Mediterranean  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE  LIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  LIMATE  Moderate  Moderate  PRODUCT RECOMMENDATION 1	Normal		Moderate
Change every 200 hours/ 3 months  USE  Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  USE  Initial service  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40  Multifleet SCD 30  Change every 50 hours  USE  INITIAL SERVICE  Moderate  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 2  Multifleet SCD 30			
Normal  PRODUCT RECOMMENDATION 1  Multifleet SCD 20W-20  Multifleet SCD 10W  Change every 200 hours/ 3 months  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  USE  USE  CLIMATE  Tropical  Multifleet SCD 40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Mediterranean  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Moderate  Moderate  PRODUCT RECOMMENDATION 2	Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Multifleet SCD 10W  Change every 200 hours/ 3 months  USE USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40  Change every 50 hours  USE USE USE USE USE USE USE USE USE US	Change every 200 hours/ 3 months		
PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Multifleet SCD 10W  Change every 200 hours/ 3 months  USE USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40  Change every 50 hours  USE USE USE USE USE USE USE USE USE US	USE		CLIMATE
Multifleet SCD 20W-20  Change every 200 hours/ 3 months  USE USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40  Change every 50 hours  USE USE USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 40  CLIMATE Mediterranean  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40  Change every 50 hours  USE USE USE USE USE USE USE USE USE US	Normal		Cold
Change every 200 hours/ 3 months  USE Initial Service Tropical  PRODUCT RECOMMENDATION 1 Multifleet SCD 40  Change every 50 hours  USE USE Initial Service PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40  Change every 50 hours  USE Initial Service PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40  Change every 50 hours  USE USE USE USE USE USE USE USE USE US	PRODUCT RECOMMENDATION 1		
Initial service Initial service  PRODUCT RECOMMENDATION 1 Multifleet SCD 40  Change every 50 hours  USE Initial service Initial service  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40  Change every 50 hours  USE INITIAL PRODUCT RECOMMENDATION 2 Multifleet SCD 30  Change every 50 hours  USE INITIAL SERVICE INITIAL SERVICE INITIAL SERVICE  PRODUCT RECOMMENDATION 2  Moderate  PRODUCT RECOMMENDATION 2	Multifleet SCD 20W-20	Multifleet SCD 10W	
Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40  Change every 50 hours  USE  CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Multifleet SCD 30  Change every 50 hours  USE  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2	Change every 200 hours/ 3 months		
Multifleet SCD 40  Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1 Multifleet SHPD 15W-40  Change every 50 hours  USE  CLIMATE Mediterranean  PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40  Change every 50 hours  USE  CLIMATE Multifleet SCD 30  Change every 50 hours  USE  CLIMATE Moderate  PRODUCT RECOMMENDATION 2	USE		CLIMATE
Multifleet SCD 40  Change every 50 hours  USE CLIMATE Initial service Mediterranean  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 Multifleet SCD 30  Change every 50 hours  USE CLIMATE Initial service Moderate  PRODUCT RECOMMENDATION 2	Initial service		Tropical
Change every 50 hours  USE Initial service PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 Multifleet SCD 30  Change every 50 hours  USE USE CLIMATE Initial service PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2  Description:  CLIMATE Moderate Moderate			
Initial service  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 2  Multifleet SCD 30  CLIMATE  Moderate  PRODUCT RECOMMENDATION 2	Multifleet SCD 40		
Initial service  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40  Multifleet SCD 30  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 2  Mediterranean  Mediterranean  CLIMATE  Moderate	Change every 50 hours		
PRODUCT RECOMMENDATION 1  Multifleet SHPD 15W-40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 2  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2	USE		CLIMATE
Multifleet SHPD 15W-40  Change every 50 hours  USE  Initial service  PRODUCT RECOMMENDATION 1  Multifleet SCD 30  CLIMATE  Moderate	Initial service		Mediterranean
Change every 50 hours  USE  CLIMATE  Initial service  PRODUCT RECOMMENDATION 1  PRODUCT RECOMMENDATION 2			
USE CLIMATE Initial service Moderate  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	Multifleet SHPD 15W-40	Multifleet SCD 30	
Initial service Moderate  PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	Change every 50 hours		
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	USE		CLIMATE
	Initial service		Moderate
Kroontrak MTH 10W-30 Multifleet SHPD 10W-40	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
	Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	

PRODUCT RECOMMENDATION

## YANMAR DIESEL ENGINES LA L60AE-S, L60A(C)E-D, L60AE-SE, L60A(C)E-DE (1995 AND AFTER)



USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 20W-20	Multifleet SCD 10W	
Change every 50 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.