

YANMAR FE FE-240H (2000 AND AFTER)

ENGINE Yanmar 3TNE78A
Capacity: 3,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Multifleet SHPD 10W-40 |

Check every 10 hours, change every 100 hours

| USE | CLIMATE |
|-------------------|----------|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-----------------------------|-------------------------------|
| Kroontrak MTH 10W-30 | Multifleet SHPD 10W-40 |

Change every 50 hours

DIFFERENTIAL FRONT
Capacity: 3,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | SP Gear 5015 |

Check every 50 hours, change every 300 hours

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING
Capacity: 18 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | SP Gear 5015 |

Check every 50 hours, change every 300 hours

COOLING SYSTEM
Capacity: 3,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|-------------------------------|--------------------------|
| Coolant -38 Organic NF | Coolant -26 |

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.