BREMACH BRICK BRICK 4X4 EURO 3 (2001-2008)



ENGINE 8140.43B Euro 3 Capacity: 6 liter, Filter capacity: 1 liter		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 15000 km/ 500 hours

DIFFERENTIAL FRONT 4x4 Capacity: 2 liter		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 15000 km/ 500 hours, change every 30000 km

DIFFERENTIAL REAR Capacity: 2 liter		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 15000 km/ 500 hours, change every 30000 km

TRANSFERBOX Capacity: 2,5 liter		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Check every 15000 km/ 500 hours, change every 30000 km

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W	

Check every 15000 km/ 500 hours, change every 30000 km

BREMACH BRICK BRICK 4X4 EURO 3 (2001-2008)



HYDRAULIC BRAKE SYSTEM Capacity: 1 liter		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
	000001	

Check every 15000 km/ 500 hours, change every 60000 km

POWER STEERING Capacity: 2 liter		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	
Ob 1		

Check every 15000 km/ 500 hours, change every 60000 km

GREASE POINTS/NIPPLES		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 15000 km/ 500 hours

COOLING SYSTEM		
USE		CLIMATE
all		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 15000 km/ 500 hours		1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.