

# CHEVROLET (USA / CAN) SILVERADO

## GMT901 SILVERADO 5.3 V8 AWD (2010-2013)



**ENGINE** LMG/LC9  
Capacity: 5,7 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

*Change every 7500 miles/ 12 months*

### DIFFERENTIAL FRONT (4x4)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 7500 miles*

### DIFFERENTIAL FRONT (4x4)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 7500 miles*

### DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 7500 miles*

# CHEVROLET (USA / CAN) SILVERADO

## GMT901 SILVERADO 5.3 V8 AWD (2010-2013)

**TRANSFERBOX (4X4)**

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 7500 miles, change every 97500 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 7500 miles, change every 45000 miles*

USE	CLIMATE
Extremely severe	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 7500 miles, change every 22500 miles***TRANSMISSION AUTOMATIC 6L80-E 6/1**

Capacity: 5,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 7500 miles, change every 97500 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Check every 7500 miles, change every 45000 miles***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 7500 miles, change every 45000 miles/ 36 months*

# CHEVROLET (USA / CAN) SILVERADO

## GMT901 SILVERADO 5.3 V8 AWD (2010-2013)



### POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

*Check every 7500 miles*

### COOLING SYSTEM

Capacity: 16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

*Check every 7500 miles, change every 150000 miles/ 60 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*