PRODUCT RECOMMENDATION

CHEVROLET (USA / CAN) SILVERADO GMT901 SILVERADO HYBRID (2009-2010)

ENGINE LFA
Capacity: 5,7 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Presteza MSP 5W-30	**Xedoz FE 5W-30**	

Change every 12 months

DIFFERENTIAL REAR
Capacity: 2,03-2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
SP Gear 1011	**Syngear TDL 75W-90**	

TRANSMISSION AUTOMATIC 4/1
Capacity: 4,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 12 months, change every 100000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 12 months, change every 50000 miles

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CHEVROLET (USA / CAN) SILVERADO GMT901 SILVERADO HYBRID (2009-2010)

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
HT Q9 High Grade Grease	**Labora Grease**	**Q5 MP Calcep Grease EP 2**

COOLING SYSTEM ENGINE
Capacity: 16,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant SP 15	**Coolant SP 15+**	

Check every 12 months, change every 150000 miles/ 60 months

COOLING SYSTEM POWER ELECTRONICS
Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant SP 15	**Coolant SP 15+**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367