

# CHRYSLER (EU) VOYAGER VOYAGER 3.3

(1996-2001)

**ENGINE**

Capacity: 4,3 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Specialsynth MSP 5W-40</b>	<b>Emperol 5W-40</b>

*Check every 1000 km, change every 12000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Specialsynth MSP 5W-40</b>	<b>Emperol 5W-40</b>

*Check every 1000 km, change every 5000 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 3,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 12000 km/ 12 months, change every 48000 km/ 48 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 12000 km/ 12 months, change every 24000 km/ 48 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 24 months*

# CHRYSLER (EU) VOYAGER VOYAGER 3.3I

## (1996-2001)



### POWER STEERING

Capacity: 0,81 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

Check every 24000 km/ 12 months

### GREASE POINTS/NIPPLES BALL JOINTS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	

Change every 24000 km/ 12 months

### GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

Change every 24000 km/ 12 months

### COOLING SYSTEM

Capacity: 12,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Change every 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Change every 48000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.