

CITROËN BERLINGO B9 BERLINGO 1.6I

16V (80 KW) NFU (2008-2012)

**ENGINE TU5JP4**

Capacity: 3,25 liter, Filter capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

Change every 30000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

*Change every 20000 km/ 12 months***TRANSAXLE MANUAL MA 5/1**

Capacity: 1,8 liter

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

*Check every 24 months/ 30000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Check every 20000 km/ 12 months, change every 60000 km/ 24 months***ELECTRO-HYDRAULIC POWER STEERING (EHPS)**

Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 24 months/ 30000 km

CITROËN BERLINGO B9 BERLINGO 1.6I

16V (80 KW) NFU (2008-2012)



HYDRAULIC POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 5,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 20000 km/ 12 months, change every 120000 km/ 60 months

AIRCONDITIONING COMPRESSOR

Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.