

CITROËN C25 C 25 D 2.5 4X4 (1989-1990)**ENGINE U25/661**

Capacity: 5,6 liter, Filter capacity: 0,7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	Multifleet SHPD 15W-40	

Change every 7500 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Change every 7500 km/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	Multifleet SHPD 15W-40	

Change every 5000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

*Change every 5000 km/ 6 months***DIFFERENTIAL REAR (4x4)**

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

*Check every 7500 km, change every 22500 km***TRANSAXLE MANUAL 5/1**

Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

Check every 7500 km, change every 22500 km

CITROËN C25 C 25 D 2.5 4X4 (1989-1990)**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
<i>Check every 1000 km, change every 67500 km/ 24 months</i>		

POWER STEERING

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
<i>Check every 22500 km</i>		

COOLING SYSTEM

Capacity: 10,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Check every 1000 km, change every 24 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.