

# CITROËN JUMPER / RELAY JUMPER / RELAY 2.0i 4X4 (1999-2002)

**ENGINE XU10J2U**

Capacity: 5 liter, Filter capacity: 0,5 liter

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Normal                   |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Avanza MSP 0W-30</b>  | <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> |

*Change every 20000 km/ 12 months***DIFFERENTIAL REAR (4x4)**

Capacity: 2,3 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gearlube LS 80W-90</b> |  |          |

*Check every 20000 km/ 12 months, change every 40000 km***TRANSAXLE MANUAL ME5TU 5/1**

Capacity: 1,85 liter

| USE                      |                            | CLIMATE  |
|--------------------------|----------------------------|----------|
| Normal                   |                            | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |          |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |          |

*Check every 60000 km***TRANSAXLE MANUAL MG5TU 5/1**

Capacity: 2,75 liter

| USE                      |                            | CLIMATE  |
|--------------------------|----------------------------|----------|
| Normal                   |                            | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |          |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |          |

*Check every 60000 km***TRANSAXLE MANUAL MLGU5 5/1**

Capacity: 2,7 liter

| USE                      |                            | CLIMATE  |
|--------------------------|----------------------------|----------|
| Normal                   |                            | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |          |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |          |

*Check every 60000 km*

# CITROËN JUMPER / RELAY JUMPER / RELAY 2.0i 4X4 (1999-2002)

**TRANSAXLE MANUAL MLUC 5/1**

Capacity: 2,4 liter (Dry fill), Capacity: 2,1 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015***Check every 60000 km***TRANSAXLE MANUAL LOW REDUCTION ME 5/1**

Capacity: 2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube RPC 75W-80***Check every 20000 km/ 12 months, change every 40000 km***TRANSAXLE MANUAL LOW REDUCTION MG 5/1**

Capacity: 3,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube RPC 75W-80***Check every 20000 km/ 12 months, change every 40000 km***TRANSFERBOX (4x4)**

Capacity: 0,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 20000 km/ 12 months, change every 40000 km***HYDRAULIC BRAKE SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 60000 km/ 24 months*

# CITROËN JUMPER / RELAY JUMPER / RELAY 2.0i 4X4 (1999-2002)



## POWER STEERING

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

Check every 20000 km/ 12 months

## COOLING SYSTEM

Capacity: 9,5 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 20000 km/ 12 months, change every 120000 km/ 60 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*