

CITROËN JUMPY / DISPATCH JUMPY / DISPATCH 2.0i 16V RFH (2007-2009)

**ENGINE EW10A**

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

*Change every 30000 km/ 24 months***TRANSAXLE MANUAL BE4R 5/1**

Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,54 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 24 months***POWER STEERING**

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

CITROËN JUMPY / DISPATCH JUMPY / DISPATCH 2.0i 16V RFH (2007-2009)



AIRCONDITIONING COMPRESSOR

Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.