FIAT (EU) DUCATO 250, 290 DUCATO 3.0 MULTIJET 160 (2006-2010)



| ENGINE F1CE0481 D Capacity: 7 liter (Service fill), Filter capacity: 1 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Emperol 5W-40 | | |
| Change every 40000 km/ 12 months | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Emperol 5W-40 | | |
| Change every 20000 km/ 12 months | | |

| HYDRAULIC ACTUATION GEARBOX Capacity: 0,7 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Fluid 3023 | |

| TRANSAXLE MANUAL M38, M40 Capacity: 2,9 liter | 6/1 | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 5015 | Syngear MT/LD 75W-80 | Syngear 75W-90 |

| TRANSAXLE SEMI-AUTOMATIC M38, M40 6/1 Capacity: 2,9 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 5015 | Syngear MT/LD 75W-80 | Syngear 75W-90 |
| | | |

FIAT (EU) DUCATO 250, 290 DUCATO 3.0 MULTIJET 160 (2006-2010)



| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,6 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| | | |

Change every 90000 km/24 months

| POWER STEERING Capacity: 1,5 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 2032 | |
| Check every 90000 km/ 12 months | |

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE

We are unable to give a standard recommendation for this component. Please contact our service department.

| GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

| COOLING SYSTEM Capacity: 11-11,9 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 14+ | |
| Check every 40000 km/ 12 months | · |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.