FIAT (EU) DUCATO 230, 244 DUCATO 1.9 D (50 KW) 230 (2000-2002)



ENGINE Capacity: 5,25 liter, Capacity: 4,25 liter (+ airconditioning), Capacity: 6,3 liter (Dry fill), Filter capacity: 0,75 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Emperol 10W-40	Bi-Turbo 15W-40	Synfleet SHPD 10W-40		

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Check every 60000 km		

HYDRAULIC BRAKE SYSTEM Capacity: 0,59 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Charles a variety 45000 kms, about an avair 400000 kms/24 magniths	

Check every 15000 km, change every 60000 km/24 months

POWER STEERING Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 15000 km	

COOLING SYSTEM Capacity: 10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 15000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

FIAT (EU) DUCATO 230, 244 DUCATO 1.9 D (50 KW) 230 (2000-2002)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.