## FIAT (EU) FIORINO FIORINO 1.3 (1988-1994)



ENGINE 146A5000 Capacity: 3,4 liter, Capacity: 3,7 liter (Dry fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 15W-40				
Check every 500 km, change every 15000 km/ 12 months				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Asyntho 5W-30	Emperol 10W-40	Synfleet SHPD 10W-40		
Check every 500 km, change every 15000 km/ 12 months				

TRANSAXLE MANUAL 5/1 Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90
Check every 30000 km, change ev	ery 120000 km	

HYDRAULIC BRAKE SYSTEM
Capacity: 0,36 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Check every 500 km, change every 24 months

COOLING SYSTEM Capacity: 5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 500 km, change every 60000 km/24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.