FIAT (EU) FIORINO FIORINO 1.7D (1994-1998)



ENGINE 149B4.000 Capacity: 5 liter, Filter capacity: 0,35 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Bi-Turbo 15W-40	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40		
Check every 500 km, change every 7500 km/ 12 months				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Emperol 10W-40	Synfleet SHPD 10W-40			

Check every 500 km, change every 7500 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 3,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 45000 km, change every 120000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,36 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 500 km, change every 24 months

COOLING SYSTEM Capacity: 8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

Check every 500 km, change every 60000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.