

FORD (EU) RANGER T6 / KE RANGER 2.2 TDCI (110 KW) (2011-2015)

**ENGINE** Duratorq, GBVAJQJ/ENQJ

Capacity: 8,9 liter (Initial fill), Capacity: 7,7-8,6 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Fuel sulfur level > 350 ppm	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 30000 km/ 24 months*

USE	CLIMATE
Fuel sulfur level < 350 ppm	Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 30000 km/ 24 months***DIFFERENTIAL REAR**

Capacity: 3-3,45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90**DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 3 liter, Capacity: 0,16 liter (Friction modifier)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90**TRANSAXLE AUTOMATIC 6R80 6/1**

Capacity: 10,5 liter (Dry fill), Capacity: 9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

PRODUCT RECOMMENDATION 2

SP Matic 2032

FORD (EU) RANGER T6 / KE RANGER 2.2 TDCI (110 KW) (2011-2015)



TRANSMISSION MANUAL MT82 6/1
Capacity: 2,6 liter, Capacity: 2,7 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

POWER STEERING

Capacity: 1,33-1,36 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

COOLING SYSTEM

Capacity: 11,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 150 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 540-675 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.