FORD (EU) TRANSIT V184/V185 TRANSIT 2.5 TDI (1998-2000)



| ENGINE TDE Capacity: 6 liter, Filter capacity: 0,3 liter | | |
|-----------------------------------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol 5W-40 | Asyntho 5W-30 | Emperol 10W-40 |

Check every 3000 km, change every 10000 km/ 12 months

| DIFFERENTIAL REAR Capacity: 1,7-2,7 liter | |
|-------------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube GL-5 80W-90 | |
| Check every 20000 km/ 12 months | · |

| TRANSMISSION AUTOMATIC AL4D 4/1 Capacity: 10,3 liter (Dry fill), Capacity: 8,2 liter (Service file) | II) |
|-----------------------------------------------------------------------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 2032 | |
| Check every 20000 km/ 12 months | · |

| TRANSMISSION MANUAL MT75 Capacity: 1,25 liter | 5/1 | | |
|--------------------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Gear 1011 | Syngear TDL 75W-90 | | |
| Check every 20000 km/ 12 months | ' | | |

| HYDRAULIC BRAKE SYSTEM | | |
|----------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Change every 60000 km/ 36 months | - | ' |

FORD (EU) TRANSIT V184/V185 TRANSIT 2.5 TDI (1998-2000)



| POWER STEERING | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 4016 | ATF Dexron II-D | |

| COOLING SYSTEM Capacity: 12 liter | | |
|-----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 11 | Coolant -38 Organic NF | Coolant -26 |
| Change every 60000 km/ 24 month | 1 | 1 |

Change every 60000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.