FORD (EU) TRANSIT V363 TRANSIT 2.2 TDCI (100) RWD (2014-2018)



ENGINE DRR5 Capacity: 10,5 liter (Initial fill), Capacity: 10,1 liter (Service fill)				
use Normal	climate Moderate			
PRODUCT RECOMMENDATION 1 Duranza LSP 5W-30				

Check every 25000 km/12 months, change every 50000 km/24 months

DIFFERENTIAL REAR Capacity: 2,85 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
	-

Check every 25000 km/ 12 months, change every 50000 km/ 24 months

TRANSMISSION MANUAL MT82 6/1 Capacity: 2,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	
Check every 50000 km/24 months	·

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid-LV Super DOT 4			

Check every 25000 km/ 12 months, change every 24 months

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Check every 50000 km/24 months		

KROON-OIL B.V. Postbus 149 7600 AC Almelo

FORD (EU) TRANSIT V363 TRANSIT 2.2 TDCI (100) RWD (2014-2018)



COOLING SYSTEM Capacity: 10-13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 50000 km/ 24 months	change every 120 months	

Check every 50000 km/24 months, change every 120 months

AIRCONDITIONING COMPRESSOR BUS

Capacity: 160-245 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR VAN

Capacity: 160-245 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 725-765 grams, Capacity: 1135-1165 grams (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM BUS

Capacity: 725-755 grams, Capacity: 1035-1065 grams (With auxiliary climate control)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.