

FORD (USA) F-150, 10TH GEN. F-150 4.2 V6 (1997-2004)

**ENGINE**

Capacity: 5,7 liter, Filter capacity: 0,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Check every 6 months, change every 8000 km*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 6000 km***DIFFERENTIAL FRONT (4x4)**

Capacity: 1,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 6 months***DIFFERENTIAL REAR C200, 4x2/4x4**

Capacity: 2,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Check every 6 months***TRANSFERBOX Borg Warner**

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 6 months, change every 96000 km*

FORD (USA) F-150, 10TH GEN. F-150 4.2 V6 (1997-2004)


TRANSMISSION AUTOMATIC 4R70W 4/1

Capacity: 6,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 6 months, change every 45000 km

TRANSMISSION MANUAL M50D 5/1

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 6 months, change every 96000 km

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 16000 km/ 6 months

POWER STEERING

Capacity: 0,91 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 6 months

FORD (USA) F-150, 10TH GEN. F-150 4.2 V6 (1997-2004)



COOLING SYSTEM

Capacity: 16,4 liter, Capacity: 14,9 liter (+ airconditioning)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 18	Coolant -26	

Check every 24000 km/ 12 months, change every 48000 km/ 36 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 18	Coolant -26	

Change every 800000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.