

FORD (USA) F-150, 12TH GEN. F-150 4.6 V8 24V (2009-2010)



ENGINE 281 CID, 3V
Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 7500 miles/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 5000 miles/ 6 months/ 200 hours

DIFFERENTIAL REAR
Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 150000 miles

DIFFERENTIAL REAR Dana
Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 105000 miles

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 2,6 liter, Capacity: 0,12 liter (LS-additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 150000 miles

FORD (USA) F-150, 12TH GEN. F-150 4.6 V8 24V (2009-2010)



DIFFERENTIAL REAR LIMITED SLIP Dana
Capacity: 2,6 liter, Capacity: 0,12 liter (LS-additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gearlube Racing 75W-140

Change every 105000 miles

TRANSMISSION AUTOMATIC 6R80 6/1
Capacity: 13,2 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
SP Matic 4036

PRODUCT RECOMMENDATION 2
SP Matic 2032

Check every 30000 miles, change every 150000 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1
SP Matic 4036

PRODUCT RECOMMENDATION 2
SP Matic 2032

Change every 30000 miles

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Drauliquid DOT 3

Check every 6 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
SP Matic 2032

Check every 6 months

FORD (USA) F-150, 12TH GEN. F-150 4.6 V8 24V (2009-2010)



GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
<i>Check every 6 months</i>		

COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	
<i>Check every 6 months, change every 45000 miles/ 36 months</i>		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	
<i>Check every 6 months, change every 105000 miles/ 72 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.