

# FORD (USA) F-150, 12TH GEN. F-150 6.2 V8 4X4 (2010-2011)



**ENGINE** 379 CID  
Capacity: 6,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

*Check every 1 months, change every 5000 miles/ 6 months*

| USE            | CLIMATE  |
|----------------|----------|
| Flexible (max) | Moderate |

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

*Check every 1 months, change every 7500 miles/ 6 months*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 1,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

*Change every 150000 miles*

**DIFFERENTIAL REAR**  
Capacity: 2,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

*Change every 150000 miles*

**DIFFERENTIAL REAR LIMITED SLIP**  
Capacity: 2,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

*Change every 150000 miles*

# FORD (USA) F-150, 12TH GEN. F-150 6.2 V8 4X4 (2010-2011)

**TRANSFERBOX**

Capacity: 1,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>SP Matic 4016</b>     | <b>ATF Dexron II-D</b>   |  |

*Change every 150000 miles*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>SP Matic 4016</b>     | <b>ATF Dexron II-D</b>   |  |

*Change every 60000 miles***TRANSMISSION AUTOMATIC 6R80 6/1**

Capacity: 12,4 liter (Dry fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>SP Matic 4036</b>     | <b>SP Matic 2032</b>     |  |

*Change every 150000 miles***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Drauliquid DOT 3</b>  |  |  |

**POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 2032</b>     |  |  |

# FORD (USA) F-150, 12TH GEN. F-150 6.2 V8 4X4 (2010-2011)

**COOLING SYSTEM**

Capacity: 18,5 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 6 months, change every 45000 miles/ 36 months*

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Initial service          |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 6 months, change every 105000 miles/ 72 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*