

# FORD (USA) F-350 (SUPER DUTY) F-350 6.7 TD SUPER DUTY (2013-2016)



**ENGINE** Power Stroke  
Capacity: 12,4 liter (Service fill)

USE	CLIMATE
Biodiesel B6-B20, Flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1

**Dieselfleet MSP 15W-40**

*Change every 10000 miles/ 12 months*

USE	CLIMATE
Biodiesel B6-B20, Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**Armado Synth MSP 5W-40**

*Change every 10000 miles/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Armado Synth MSP 5W-40**

*Change every 7500 miles/ 300 hours/ 6 months*

USE	CLIMATE
Flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1

**Dieselfleet MSP 15W-40**

*Change every 10000 miles/ 12 months*

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**Armado Synth MSP 5W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet MSP 10W-30**

*Change every 10000 miles/ 12 months*

USE	CLIMATE
Normal, fuel sulfur level > 500 ppm	Mediterranean

PRODUCT RECOMMENDATION 1

**Dieselfleet MSP 15W-40**

*Change every 2500 miles/ 3 months*

USE	CLIMATE
Normal, fuel sulfur level > 500 ppm	Moderate

PRODUCT RECOMMENDATION 1

**Armado Synth MSP 5W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet MSP 10W-30**

*Change every 2500 miles/ 3 months*

# FORD (USA) F-350 (SUPER DUTY) F-350 6.7 TD SUPER DUTY (2013-2016)



USE		CLIMATE
Normal, fuel sulfur level 15-500 ppm		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Dieselfleet MSP 15W-40</b>		

*Change every 5000 miles/ 6 months*

USE		CLIMATE
Normal, fuel sulfur level 15-500 ppm		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Armado Synth MSP 5W-40</b>	<b>Dieselfleet MSP 10W-30</b>	

*Change every 5000 miles/ 6 months*

DIFFERENTIAL REAR CONVENTIONAL Dana M80 Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	

*Change every 100000 miles*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	

*Change every 50000 miles*

DIFFERENTIAL REAR CONVENTIONAL Ford 10.5 Capacity: 3,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 150000 miles*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 100000 miles*



# FORD (USA) F-350 (SUPER DUTY) F-350 6.7 TD SUPER DUTY (2013-2016)


**DIFFERENTIAL REAR LIMITED SLIP** Ford 10.5

Capacity: 3,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 150000 miles*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube Racing 75W-140</b>		

*Change every 100000 miles*
**TRANSMISSION AUTOMATIC** 6R140(W) 6/1

Capacity: 15,8-17,5 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 4036</b>	<b>SP Matic 2032</b>	

*Change every 150000 miles*
**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid DOT 3</b>	

**POWER STEERING**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

# FORD (USA) F-350 (SUPER DUTY) F-350 6.7 TD SUPER DUTY (2013-2016)



## COOLING SYSTEM PRIMARY

Capacity: 27,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

*Check every 6 months, change every 45000 miles/ 36 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

*Check every 6 months, change every 105000 miles/ 72 months*

## COOLING SYSTEM SECONDARY

Capacity: 11,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

*Check every 6 months, change every 45000 miles/ 36 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15</b>	<b>Coolant SP 15+</b>	

*Check every 6 months, change every 105000 miles/ 72 months*

## AIRCONDITIONING

Capacity: 740 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING COMPRESSOR

Capacity: 104 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 22,7 liter (Cabin/Chassis model), Capacity: 18,9 liter (Pick-up model)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*