

FORD (USA) F-350 (SUPER DUTY) F-350 6.8 V10 SUPER DUTY (2011-2013)



ENGINE Triton
Capacity: 6,6 liter

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Change every 5000 miles/ 6 months

USE
Flexible (max)

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Check every 1 months, change every 7500 miles/ 6 months

DIFFERENTIAL REAR CONVENTIONAL Dana M80
Capacity: 4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Change every 105000 miles

DIFFERENTIAL REAR CONVENTIONAL Ford 10.5
Capacity: 3,3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 150000 miles

DIFFERENTIAL REAR LIMITED SLIP Ford 10.5
Capacity: 3,3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 150000 miles

FORD (USA) F-350 (SUPER DUTY) F-350 6.8 V10 SUPER DUTY (2011-2013)


TRANSMISSION AUTOMATIC 5R110W 5/1

Capacity: 16,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

Change every 60000 miles

TRANSMISSION AUTOMATIC 6R140(W) 6/1

Capacity: 15,8-17,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

Change every 150000 miles

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

FORD (USA) F-350 (SUPER DUTY) F-350 6.8 V10 SUPER DUTY (2011-2013)



COOLING SYSTEM

Capacity: 25,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 45000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 6 months, change every 105000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.