## GMC (USA / CAN) SONOMA GMT325 SONOMA 4.3 (2000-2000)



| <b>ENGINE</b> LU3 Vortec<br>Capacity: 4,3 liter |                          |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                        | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30                                   | Emperol 10W-40           | Synfleet SHPD 10W-40     |
| Change every 7500 miles/ 12 months              |                          |                          |
| USE   |                          | CLIMATE                  |
| Severe  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                        | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30                                   | Emperol 10W-40           | Synfleet SHPD 10W-40     |
| Channe aver 2000 miles / 2 months               |                          | ·                        |

Change every 3000 miles/ 3 months

| <b>DIFFERENTIAL REAR</b><br>Capacity: 1,9 liter |          |
|---|----------|
| USE   | CLIMATE  |
| Normal  | Moderate |
| PRODUCT RECOMMENDATION 1                        |          |
| Gearlube LS 80W-90                              |          |
| Check every 7500 miles                          |          |

| USE  |  | CLIMATE  |
|--|--|----------|
| Severe   |  | Moderate |
| PRODUCT RECOMMENDATION 1                         |  |          |
| Gearlube LS 80W-90                               |  |          |
| Check every 3000 miles, change every 15000 miles |  |          |

| TRANSMISSION AUTOMATIC 4L60-E 4/1<br>Capacity: 4,7 liter |   |                     |
|--|---|---------------------|
| use<br>Normal  |   | climate<br>Moderate |
| PRODUCT RECOMMENDATION 1 SP Matic 2032                   | PRODUCT RECOMMENDATION 2<br>ATF Almirol |                     |

Change every 50000 miles

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Severe                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 2032            | ATF Almirol              |          |
| Change avery 15000 miles |                          |          |

Change every 15000 miles

## GMC (USA / CAN) SONOMA GMT325 SONOMA 4.3 (2000-2000)



## TRANSMISSION MANUAL 5/1

We are unable to give a standard recommendation for this component. Please contact our service department.

| HYDRAULIC BRAKE SYSTEM   |  |          |
|--------------------------|--|----------|
| USE                      |  | CLIMATE  |
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| Drauliquid DOT 3         |  |          |
| 01 01 11                 |  | ·        |

Change every 24 months

| HYDRAULIC CLUTCH SYSTEM  |  |          |
|--------------------------|--|----------|
| USE                      |  | CLIMATE  |
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| Drauliquid DOT 3         |  |          |
|                          |  |          |

| POWER STEERING           |          |          |
|--------------------------|----------|----------|
| USE                      |          | CLIMATE  |
| Normal                   |          | Moderate |
| PRODUCT RECOMMENDATION 1 |          |          |
| SP Matic 2032            |          |          |
|                          | <u>I</u> |          |

Check every 7500 miles

| COOLING SYSTEM<br>Capacity: 11,1 liter |                          |          |
|--|--------------------------|----------|
| USE                                    |                          | CLIMATE  |
| Normal                                 |                          | Moderate |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15                          | Coolant SP 15+           |          |
| Change every 150000 miles/ 60 months   |                          |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.