

HYUNDAI (EU) H 100 H 100 2.4 (1993-2000)**ENGINE G4CS**

Capacity: 3,9 liter, Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Bi-Turbo 15W-40	Bi-Turbo 20W-50	HDX 20W-50

Change every 15000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Change every 15000 km/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-40	Asyntho 5W-30	

Change every 15000 km/ 12 months

USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Bi-Turbo 15W-40	Bi-Turbo 20W-50	HDX 20W-50

Change every 5000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Change every 5000 km

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 5W-40	Asyntho 5W-30	

Change every 5000 km

HYUNDAI (EU) H 100 H 100 2.4 (1993-2000)**DIFFERENTIAL REAR**

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

TRANSMISSION AUTOMATIC 4/1

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 30000 km/ 24 months, change every 45000 km/ 36 months

TRANSMISSION MANUAL 5/1

Capacity: 2 liter

USE		CLIMATE
->2005		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

USE		CLIMATE
2005->		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 15000 km/ 12 months, change every 120000 km/ 24 months

HYUNDAI (EU) H 100 H 100 2.4 (1993-2000)**POWER STEERING**

Capacity: 0,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 24 months/ 30000 km

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 2

MP Lithep Grease EP 2

Check every 15000 km/ 12 months, change every 60000 km/ 48 months

COOLING SYSTEM

Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.