

# HYUNDAI (EU) SANTA FE DM SANTA FE 2.2 CRDI VGT DPF (2013-2014)

**ENGINE (R-SERIES)**

Capacity: 7,3-7,8 liter (Dry fill), Capacity: 6,3-6,7 liter (Service fill), Filter capacity: 0,7 liter

| USE                              | CLIMATE  |
|----------------------------------|----------|
| Normal, fuel according to EN 590 | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
|-----------------------------|-----------------------------|---------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> |

*Check every 500 km, change every 30000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
|-----------------------------|-----------------------------|---------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> |

*Check every 500 km, change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC A6LF3 6/1**

Capacity: 7,7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 4036</b>     |  |  |

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 4036</b>     |  |  |

*Change every 90000 km***TRANSAXLE MANUAL M6LF1 6/1**

Capacity: 1,8-1,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| <b>SP Gear 5015</b>      | <b>Syngear MT/LD 75W-80</b> | <b>Syngear 75W-90</b>    |

*Check every 48 months/ 60000 km*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
|--------------------------|-----------------------------|--------------------------|
| <b>SP Gear 5015</b>      | <b>Syngear MT/LD 75W-80</b> | <b>Syngear 75W-90</b>    |

*Check every 60000 km/ 48 months, change every 120000 km*

# HYUNDAI (EU) SANTA FE DM SANTA FE 2.2

## CRDI VGT DPF (2013-2014)



### HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

Change every 30000 km/ 24 months

### POWER STEERING

Capacity: 1 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

Check every 24 months/ 30000 km

### COOLING SYSTEM

Capacity: 9,1-9,3 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Change every 30000 km/ 24 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| First change only        |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.