

IVECO DAILY 35 DAILY 35 S 10 (2006-2009)**ENGINE F1AE0481A-HPI**

Capacity: 5,7 liter, Filter capacity: 1,4 liter (+ heat exchanger)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza LSP 5W-30	Asyntho 5W-30

Change every 40000 km/ 800 hours/ 12 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

*Change every 40000 km/ 800 hours/ 12 months***DIFFERENTIAL REAR NDA R.S.**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 40000 km/ 12 months/ 800 hours, change every 80000 km/ 24 months/ 1600 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

*Check every 40000 km/ 12 months/ 800 hours, change every 80000 km/ 24 months/ 1600 hours***TRANSMISSION MANUAL ZF 5S-300 5/1**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	Syngear MT/LD 75W-80

Check every 40000 km/ 12 months/ 800 hours, change every 120000 km/ 36 months/ 2400 hours

**HYDRAULIC BRAKE SYSTEM**

Capacity: 1,11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 40000 km/ 12 months/ 800 hours, change every 24 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 40000 km/ 12 months/ 800 hours, change every 24 months

POWER STEERING

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 40000 km/ 12 months/ 800 hours

COOLING SYSTEM

Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.