

LDV CONVOY DIESEL / V400 CONVOY 2.5 TDI (1996-2001)

**ENGINE**

Capacity: 7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Emperol 10W-40****PRODUCT RECOMMENDATION 2****Synfleet SHPD 10W-40***Change every 20000 km/ 12 months***DIFFERENTIAL REAR (4x2)**

Capacity: 2,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 20000 km/ 12 months***TRANSMISSION MANUAL MT75 5/1**

Capacity: 1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90***Check every 20000 km/ 12 months***HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 40000 km/ 48 months***HYDRAULIC CLUTCH SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4**

LDV CONVOY DIESEL / V400 CONVOY 2.5 TDI (1996-2001)



POWER STEERING

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 20000 km/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Check every 20000 km

SWIVEL PIN HOUSINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Check every 20000 km

COOLING SYSTEM

Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Check every 60000 km/ 12 months, change every 120000 km/ 24 months

STEERING MANUAL

Capacity: 0,45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.