MERCEDES-BENZ (EU) SPRINTER 906 SPRINTER 209 CDI 906 (2006-2009)



ENGINE OM646 DE22 Capacity: 11 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

DIFFERENTIAL REAR Capacity: 2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service. Change every 320000 km/ 120 months

TRANSMISSION AUTOMATIC 722.683 (* Capacity: 7,1 liter	N5A380) 5/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
TI: I:I: I II A00.00T		

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service. Change every 120000 km

TRANSMISSION MANUAL 711.6xx (NSG370) 6/1 Capacity: 1,5-2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service. Change every 320000 km/ 120 months

MERCEDES-BENZ (EU) SPRINTER 906 SPRINTER 209 CDI 906 (2006-2009)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service. Change every 24 months

CLIMATE
Moderate
MENDATION 2 PRODUCT RECOMMENDATION 3
ATF Dexron II-D

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

1		1
Coolant SP 11	Coolant SP 12 EVO	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
COOLING SYSTEM Capacity: 9,5-10 liter		

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service. Check every 12 months, change every 320000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.