MERCEDES-BENZ (EU) VARIO 667, 668, 670 VARIO 613D EURO 4 668.35X / 668.32X



(2006-2009)

ENGINE OM904LA IV Capacity: 15,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 12 months

DIFFERENTIAL REAR Capacity: 5,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
Change every 90000 km/ 1800 hou	ırs	

TRANSMISSION MANUAL G 56-6 Capacity: 6,5 liter	5 6/1		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-4 80W	Gearlube GL-4 80W-90		
Change avany 00000 km/ 1900 hay	1	-	

Change every 90000 km/ 1800 hours

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 36 months	'

HYDRAULIC CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 36 months	·

MERCEDES-BENZ (EU) VARIO 667, 668, 670 VARIO 613D EURO 4 668.35X / 668.32X



(2006-2009)

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF Dexron II-D

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

GREASE POINTS/NIPPLES WHEEL Capacity: 80 grams	BEARINGS FRONT	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 24 months	·	

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 24 months	'	,

COOLING SYSTEM Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant SP 11
Change every 36 months	1	1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.