## MERCEDES-BENZ (EU) VARIO 667, 668, 670 VARIO 813D EURO 4 670.35X / 670.32X



(2006-2009)

| ENGINE OM904LA IV<br>Capacity: 15,8 liter |                               |                          |
|---|-------------------------------|--------------------------|
| USE                                       |                               | CLIMATE                  |
| Normal                                    |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| Armado Synth LSP Ultra 5W-30              | Armado Synth LSP Ultra 10W-40 | Armado Synth LSP 10W-40  |

Change every 12 months

| DIFFERENTIAL REAR<br>Capacity: 5,2 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE                                      |                          | CLIMATE                  |
| Normal                                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011                             | Syngear TDL 75W-90       | Gearlube GL-5 80W-90     |
| Change every 90000 km/ 1800 hou          | ırs                      |                          |

| TRANSMISSION MANUAL G 56-6<br>Capacity: 6,5 liter | 5 6/1                    |          |
|---|--------------------------|----------|
| USE   |                          | CLIMATE  |
| Normal  |                          | Moderate |
| PRODUCT RECOMMENDATION 1                          | PRODUCT RECOMMENDATION 2 |          |
| Gearlube GL-4 80W                                 | Gearlube GL-4 80W-90     |          |
| Change every 90000 km/ 1800 hou                   | irs                      | ,        |

| HYDRAULIC BRAKE SYSTEM   |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Drauliquid-S DOT 4       |          |
| Change every 36 months   | ·        |

| HYDRAULIC CLUTCH SYSTEM  |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Drauliquid-S DOT 4       |          |
| Change every 36 months   |          |

## MERCEDES-BENZ (EU) VARIO 667, 668, 670 VARIO 813D EURO 4 670.35X / 670.32X



(2006-2009)

| POWER STEERING           |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 4026            | SP Matic 2032            | ATF Dexron II-D          |

| GREASE POINTS/NIPPLES    |                          |          |  |
|--------------------------|--------------------------|----------|--|
| USE                      |                          | CLIMATE  |  |
| Normal                   |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |  |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |          |  |

| GREASE POINTS/NIPPLES WHEEL Capacity: 80 grams | BEARINGS FRONT           |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 |          |
| Q5 MP Calcep Grease EP 2                       | MP Lithep Grease EP 2    |          |
| Change every 24 months                         | ·                        |          |

| GREASE POINTS/NIPPLES WHEEL BEARINGS REAR |                          |          |
|---|--------------------------|----------|
| USE                                       |                          | CLIMATE  |
| Normal                                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2 |          |
| Q5 MP Calcep Grease EP 2                  | MP Lithep Grease EP 2    |          |
| Change every 24 months                    | '                        | ,        |

| COOLING SYSTEM Capacity: 13 liter |                          |                          |
|-----------------------------------|--------------------------|--------------------------|
| USE                               |                          | CLIMATE                  |
| Normal                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+                    | Coolant SP 12            | Coolant SP 11            |
| Change every 36 months            | 1                        | I                        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.