

MERCEDES-BENZ (EU) VITO 639 VITO 109 CDI (2005-2007)



ENGINE OM646.983
Capacity: 9 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar SP LL-03 0W-30****PRODUCT RECOMMENDATION 2****Helar SP LL-03 5W-30****PRODUCT RECOMMENDATION 3****Presteza MSP 5W-30**

DIFFERENTIAL REAR
Capacity: 1,3 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1071****PRODUCT RECOMMENDATION 2****Gearlube LS 80W-90***Change every 120 months*

TRANSMISSION MANUAL 716.637 6/1
Capacity: 1,2 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015***Change every 120 months*

TRANSMISSION MANUAL 716.652 6/1
Capacity: 1,5 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015***Change every 120 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,8 liter, Capacity: 1 liter (Brake system + ESP)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-S DOT 4***Change every 24 months*

MERCEDES-BENZ (EU) VITO 639 VITO 109 CDI (2005-2007)



POWER STEERING

Capacity: 0,8-1 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

COOLING SYSTEM

Capacity: 8,6 liter, Capacity: 10,5 liter (Vito/Viano CDI type 639 + code H13/HZ7)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.