

# MERCEDES-BENZ (EU) VITO 639 VITO 111

## CDI DPF 4X4 (2007-2010)



**ENGINE** OM646 DE22  
Capacity: 9 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar SP LL-03 0W-30</b>	<b>Helar SP LL-03 5W-30</b>	<b>Presteza MSP 5W-30</b>

**DIFFERENTIAL FRONT**  
Capacity: 0,65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	

**DIFFERENTIAL REAR**  
Capacity: 1,3 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1071</b>	<b>Gearlube LS 80W-90</b>	

*Change every 120 months*

**TRANSFERBOX**  
Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

# MERCEDES-BENZ (EU) VITO 639 VITO 111

## CDI DPF 4X4 (2007-2010)


**TRANSMISSION AUTOMATIC 722.6xx 5/1**

Capacity: 7,6 liter (Initial fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026***Change every 120000 km*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4026***Change every 45000 km/ 24 months*
**TRANSMISSION MANUAL 716.637 6/1**

Capacity: 1,2 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 5015***Change every 120 months*
**TRANSMISSION MANUAL 716.652 6/1**

Capacity: 1,5 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 5015***Change every 120 months*
**HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,8 liter, Capacity: 1 liter (Brake system + ESP)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4***Change every 24 months*

# MERCEDES-BENZ (EU) VITO 639 VITO 111

## CDI DPF 4X4 (2007-2010)



### POWER STEERING

Capacity: 0,8-1 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 4026</b>	<b>SP Matic 2032</b>	

### COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 11</b>	<b>Coolant SP 12 EVO</b>	

*Change every 250000 km/ 180 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*