Duranza LSP 5W-30

### MITSUBISHI (EU) L200 L200 2.5 DI-D 4X2 (100 KW) (2009-2016)



Bi-Turbo 15W-40

# ENGINE 4D56 Capacity: 6,4-7,4 liter (Dry fill), Capacity: 0,1 liter (Oil cooler), Capacity: 5,5-6,5 liter (Service fill), Filter capacity: 0,8 liter use cLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

Asyntho 5W-30

<b>DIFFERENTIAL REAR</b> Capacity: 1,5-2,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

TRANSMISSION AUTOMATIC 4/1 Capacity: 9,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

TRANSMISSION MANUAL 5/1 Capacity: 2,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max	.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

## MITSUBISHI (EU) L200 L200 2.5 DI-D 4X2 (100 KW) (2009-2016)



HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

POWER STEERING Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

COOLING SYSTEM Capacity: 8,2 liter, Capacity: 0,65 liter (Reserve tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

#### AIRCONDITIONING COMPRESSOR Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

#### AIRCONDITIONING SYSTEM

Capacity: 480-520 grams, Capacity: 535-575 grams (Double Cab)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.