

# OPEL MOVANO A X70 MOVANO 2.5 CDTI (73 KW) (2003-2006)

**ENGINE** G9U 750, 754

Capacity: 8 liter, Filter capacity: 0,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Helar 0W-40****PRODUCT RECOMMENDATION 2****Emperol 5W-40****PRODUCT RECOMMENDATION 3****Asyntho 5W-30***Change every 40000 km/ 24 months***TRANSAXLE MANUAL** PK5 5/1

Capacity: 2,25-2,55 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 5015***Check every 40000 km/ 24 months***TRANSAXLE SEMI-AUTOMATIC** PA6 MTA 6/1

Capacity: 2,35-2,65 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 5015***Check every 40000 km/ 24 months***HYDRAULIC ACTUATION TECSHIFT**

Capacity: 0,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Fluid 3023***Check every 40000 km/ 24 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,7 liter, Capacity: 1 liter (ABS)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 40000 km/ 24 months, change every 120000 km/ 48 months*

# OPEL MOVANO A X70 MOVANO 2.5 CDTi (73 KW) (2003-2006)



## POWER STEERING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

Check every 40000 km/ 24 months

## COOLING SYSTEM

Capacity: 10 liter (Dry fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15**

PRODUCT RECOMMENDATION 2

**Coolant SP 15+**

Check every 40000 km/ 24 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.