

OPEL VIVARO A X83 VIVARO A 2.0 CDTI (84 KW) EURO 4 (2006-2008)



ENGINE M9R 780
Capacity: 6,6-7,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|-------------------------------|--------------------------|
| Presteza MSP 5W-30 | Specialsynth MSP 5W-40 | Helar 0W-40 |

Change every 30000 km/ 12 months

TRANSAXLE MANUAL PF6 6/1
Capacity: 2,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Gear 5015 | | |

Check every 12 months/ 30000 km

TRANSAXLE SEMI-AUTOMATIC PF6R MTA 6/1
Capacity: 2,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Gear 5015 | | |

Check every 12 months/ 30000 km

HYDRAULIC ACTUATION TECSHIFT
Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Fluid 3023 | | |

Check every 12 months/ 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|---------------------------|--|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Check every 30000 km/ 24 months, change every 120000 km/ 48 months

OPEL VIVARO A X83 VIVARO A 2.0 CDTI (84 KW) EURO 4 (2006-2008)



POWER STEERING

Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 2032 | ATF Almirol | |

Check every 24 months/ 30000 km

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15 | Coolant SP 15+ | |

Check every 30000 km/ 24 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.