

OPEL VIVARO B X82 VIVARO B 1.6 BITURBO CDTI (88 KW) (2014-2016)



ENGINE R9M 450 (LWU, LWY)
Capacity: 7,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 5W-30	Presteza MSP 5W-30	

Change every 40000 km/ 12 months

TRANSAXLE MANUAL PF6 6/1
Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 40000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 40000 km/ 24 months, change every 120000 km/ 48 months

POWER STEERING
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 40000 km/ 12 months

COOLING SYSTEM
Capacity: 9,5 liter, Capacity: 11 liter (+ additional heater + pre-heater)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 40000 km/ 24 months, change every 160000 km/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

**OPEL VIVARO B X82 VIVARO B 1.6
BITURBO CDTI (88 KW) (2014-2016)**



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.