PEUGEOT BIPPER A9 BIPPER 1.4I (2009-2012)



ENGINE TU3A Capacity: 3 liter		
use Normal		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30
Change every 30000 km/ 24 month	es :	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30
Change every 20000 km/ 12 month	IS	,

TRANSAXLE MANUAL MA5 5/1 Capacity: 2,1 liter (Dry fill), Capacity: 2 liter (Service fill)				
use Normal		сымате Moderate		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	Gearlube RPC 75W-80			

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Drauliquid-LV Super DOT 4				
Change every 24 months	·			

POWER STEERING Capacity: 0,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Check every 12 months/ 30000 km	

PEUGEOT BIPPER A9 BIPPER 1.4I (2009-2012)



COOLING SYSTEM Capacity: 5,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 30000 km	•	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.