PEUGEOT PARTNER B9 PARTNER 1.6I 16V (80 KW) NFU (2008-2012)



ENGINE TU5JP4 Capacity: 3,25 liter, Filter capacity: 0,25 liter				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30		

TRANSAXLE MANUAL MA 5/1 Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube RPC 75W-80		
Check every 24 months/ 30000 km			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		

Gearlube RPC 75W-80

SP Gear 5015

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Drauliquid-LV Super DOT 4				
Check every 30000 km, change every 24 months				
USE	CLIMATE			
Severe	Moderate			
PRODUCT RECOMMENDATION 1				

Drauliquid-LV Super DOT 4

Check every 20000 km, change every 24 months

PEUGEOT PARTNER B9 PARTNER 1.6I 16V (80 KW) NFU (2008-2012)



ELECTRO-HYDRAULIC POWER STEERING (EHPS) Capacity: 1,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Fluid 3013				
Check every 24 months/ 30000 km				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Fluid 3013				
Check every 20000 km/ 12 months				

HYDRAULIC POWER STEERING			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			

COOLING SYSTEM Capacity: 5,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 24 months/ 30000 km	

USE CLIMATE
Severe Moderate
PRODUCT RECOMMENDATION 1
Coolant SP 14+
Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.