DODGE RAM (USA / CAN) RAM SRT-10 DR/DH/D1 RAM SRT-10 8.3 V10 (USA) DR/DH/D1/DC/DM (2005-2005)



ENGINE Viper V10 Capacity: 8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Specialsynth MSP 5W-40	Helar 0W-40			
Change every 10000 km/ 6 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Specialsynth MSP 5W-40	Helar 0W-40			
Change every 5000 km/ 3 months				

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 147 CM3 (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC 48RE 4/1 Capacity: 13,7-15,61 liter (Dry fill), Capacity: 3,79 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				
Change every 160000 km				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				
Change every 48000 km				

TRANSMISSION MANUAL Tremec T-56 6/1				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 1071				

PRODUCT RECOMMENDATION

HYDRAULIC BRAKE SYSTEM

DODGE RAM (USA / CAN) RAM SRT-10 DR/DH/D1 RAM SRT-10 8.3 V10 (USA) DR/DH/D1/DC/DM (2005-2005)



USE	d	CLIMATE
Normal	Ŋ	Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
HYDRAULIC CLUTCH SYSTEM		
USE	q	CLIMATE
Normal	Ŋ	Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
POWER STEERING		
USE	q	CLIMATE
Normal	Ŋ	Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 160000 km		
COOLING SYSTEM Capacity: 19 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Change every 60 months

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

Change every 163000 km

USE

Severe

CLIMATE

Moderate