

RAM TRUCKS (USA / CAN) RAM 1500 (CLASSIC) DS RAM 1500 3.0 V6 D (4X4) DS (2014-2015)



ENGINE VM EcoDiesel
Capacity: 10 liter

| USE | CLIMATE |
|----------------|----------|
| Flexible (max) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------------------|-------------------------------|
| Armado Synth LSP Ultra 10W-40 | Armado Synth MSP 5W-40 |

Change every 10000 miles/ 12 months

| USE | CLIMATE |
|------------------|----------|
| Biodiesel B6-B20 | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|--------------------------------------|-------------------------------|
| Armado Synth LSP Ultra 10W-40 | Armado Synth MSP 5W-40 |

Change every 8000 miles/ 6 months

DIFFERENTIAL FRONT 215FD
Capacity: 1,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Gear 1071 | |

Check every 20000 miles/ 24 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------|--|
| SP Gear 1071 | |

Change every 20000 miles/ 24 months

DIFFERENTIAL REAR C235
Capacity: 2,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------------|--|
| Gearlube Racing 75W-140 | |

Check every 20000 miles/ 24 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | |
|--------------------------------|--|
| Gearlube Racing 75W-140 | |

Change every 20000 miles/ 24 months

RAM TRUCKS (USA / CAN) RAM 1500 (CLASSIC) DS RAM 1500 3.0 V6 D (4X4) DS (2014-2015)



DIFFERENTIAL REAR LIMITED SLIP C235 LS
Capacity: 2,1 liter, Capacity: 148 CM3 (LS-additive)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Check every 20000 miles/ 24 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 20000 miles/ 24 months*

TRANSFERBOX BW44-44
Capacity: 1,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Check every 30000 miles/ 36 months, change every 120000 miles/ 144 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 60000 miles/ 72 months*

TRANSMISSION AUTOMATIC ZF 8HP70 8/1
Capacity: 8,3 liter (Dry fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2034**HYDRAULIC BRAKE SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

RAM TRUCKS (USA / CAN) RAM 1500 (CLASSIC) DS RAM 1500 3.0 V6 D (4X4) DS (2014-2015)



COOLING SYSTEM

Capacity: 11 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Change every 150000 miles/ 120 months*

DIESEL EXHAUST FLUID

Capacity: 30,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.