RAM TRUCKS (USA / CAN) RAM 2500/3500 DJ/D2/DD RAM 2500/3500 5.7 V8 (4X2) DJ



(2013-2014)

ENGINE HEMI Capacity: 6,6 liter				
USE		CLIMATE		
Severe, =>6.3t		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Presteza MSP 5W-30	Xedoz FE 5W-30			
Change every 4000 miles				
USE		CLIMATE		
Severe, =<6.3t		Moderate		
PRODUCT RECOMMENDATION 1				
Duranza ECO 5W-20				
Change every 4000 miles				
USE		CLIMATE		
Flexible (max) =>6.3t		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Presteza MSP 5W-30	Xedoz FE 5W-30			
Change every 10000 miles/ 12 months				
USE		CLIMATE		
Flexible (max) =<6.3t		Moderate		
PRODUCT RECOMMENDATION 1				
Duranza ECO 5W-20				
Change every 10000 miles/ 12 months				
DIFFERENTIAL REAR				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 1071				
Check every 20000 miles/ 24 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 1071				
Change every 20000 miles/ 24 months				

RAM TRUCKS (USA / CAN) RAM 2500/3500 DJ/D2/DD RAM 2500/3500 5.7 V8 (4X2) DJ



(2013-2014)

(2013-2014)		
DIFFERENTIAL REAR LIMITED SLIP		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
Check every 20000 miles/ 24 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
Change every 20000 miles/ 24 months		
TRANSMISSION AUTOMATIC 66RFE 6/2 Capacity: 5,2 liter (Service fill)	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 144 months/ 120000 miles		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 60000 miles/ 72 months		
HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
		1

RAM TRUCKS (USA / CAN) RAM 2500/3500 DJ/D2/DD RAM 2500/3500 5.7 V8 (4X2) DJ



(2013-2014)

COOLING SYSTEM Capacity: 17,7-18,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 150000 miles/ 120 n	nonths	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.