

RENAULT (EU) MASCOTT MASCOTT 110 DCI (2001-2004)



ENGINE 8140.43B (110 dCi)
Capacity: 6,3 liter, Filter capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 10W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Change every 30000 km/ 24 months

DIFFERENTIAL REAR 569
Capacity: 4,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

DIFFERENTIAL REAR 669
Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

POWER TAKE OFF Hydrocar 20 Z1
Capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Syngear MT/LD 75W-80	

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

RENAULT (EU) MASCOTT MASCOTT 110 DCI (2001-2004)


TRANSMISSION MANUAL ZF S5-200 5/1

Capacity: 2,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 12 months

POWER STEERING

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 24 months/ 30000 km

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Change every 30000 km/ 24 months

RENAULT (EU) MASCOTT MASCOTT 110 DCI (2001-2004)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q7 MP Calcep Grease WR 2	Caliplex HD Grease EP 2

Change every 30000 km/ 24 months

WHEEL BEARINGS REAR OIL LUBRICATED

Capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

COOLING SYSTEM

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Check every 12 months, change every 400000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.