

# RENAULT (EU) MASCOTT MASCOTT 140 DCI (2001-2004)



**ENGINE** 8140.43K (140 dCi)  
Capacity: 6,3 liter, Filter capacity: 1,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
|----------------------------|-----------------------------|---------------------------|
| <b>Armado Synth 10W-40</b> | <b>Synfleet SHPD 10W-40</b> | <b>Armado Synth 5W-30</b> |

*Change every 30000 km/ 24 months*

**DIFFERENTIAL REAR** 569  
Capacity: 4,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3  |
|-----------------------------|------------------------------------|---------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube LS 80W-90</b> |

*Check every 30000 km/ 24 months, change every 240000 km/ 24 months*

**DIFFERENTIAL REAR** 669  
Capacity: 5,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3  |
|-----------------------------|------------------------------------|---------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube LS 80W-90</b> |

*Check every 30000 km/ 24 months, change every 240000 km/ 24 months*

**POWER TAKE OFF** Hydrocar 20 Z2  
Capacity: 0,5 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Multifleet SCD 40</b> |  |  |

*Check every 30000 km/ 24 months, change every 240000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |  |
|--------------------------|-----------------------------|--|
| <b>Multifleet SCD 30</b> | <b>Syngear MT/LD 75W-80</b> |  |

*Check every 30000 km/ 24 months, change every 240000 km/ 24 months*

# RENAULT (EU) MASCOTT MASCOTT 140 DCI (2001-2004)



## TRANSMISSION MANUAL ZF S6-300 6/1

Capacity: 2,7 liter

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Multifleet SCD 40</b> |  |               |

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

| USE                      |                             | CLIMATE  |
|--------------------------|-----------------------------|----------|
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| <b>Multifleet SCD 30</b> | <b>Syngear MT/LD 75W-80</b> |          |

Check every 30000 km/ 24 months, change every 240000 km/ 24 months

## HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Change every 12 months

## POWER STEERING

Capacity: 1,5 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

Check every 24 months/ 30000 km

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Change every 30000 km/ 24 months

# RENAULT (EU) MASCOTT MASCOTT 140 DCI (2001-2004)



## GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| USE                      |                                 | CLIMATE                        |
|--------------------------|---------------------------------|--------------------------------|
| Normal                   |                                 | Moderate                       |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3       |
| <b>Labora Grease</b>     | <b>Q7 MP Calcep Grease WR 2</b> | <b>Caliplex HD Grease EP 2</b> |

*Change every 30000 km/ 24 months*

## WHEEL BEARINGS REAR OIL LUBRICATED

Capacity: 0,2 liter

| USE                         |                                    | CLIMATE                   |
|-----------------------------|------------------------------------|---------------------------|
| Normal                      |                                    | Moderate                  |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube LS 80W-90</b> |

*Check every 30000 km/ 24 months, change every 240000 km/ 24 months*

## COOLING SYSTEM

Capacity: 12 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 16</b>     |  |          |

*Check every 12 months, change every 400000 km/ 36 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*