RENAULT (EU) MASTER II X70 MASTER II 2.5 D (1999-2007)



Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
ENGINE S8U Capacity: 6,5 liter		

Change every 20000 km/24 months

TRANSAXLE MANUAL 5/1 Capacity: 2,55-2,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Check every 60000 km	-

LIFT HYDRAULIC SYSTEM Capacity: 4,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 48 months	-

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 20000 km/ 24 months, change every 120000 km/ 48 months		

POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

Check every 20000 km/24 months

RENAULT (EU) MASTER II X70 MASTER II **2.5 D** (1999-2007)



COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		
Check every 20000 km/24 months, change every 120000 km/48 months		

Check every 20000 km/ 24 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.